

Northumbria Research Link

Citation: Jovanovic, Milutin and Betz, Robert (2001) Control strategies for brushless doubly fed reluctance machines. IEEJ Transactions on Industry Application, 121 (2). pp. 272-278. ISSN 0913-6339

Published by: Institute of Electrical Engineers of Japan

URL: <http://dx.doi.org/10.1541/ieejias.121.272> <<http://dx.doi.org/10.1541/ieejias.121.272>>

This version was downloaded from Northumbria Research Link:
<http://nrl.northumbria.ac.uk/238/>

Northumbria University has developed Northumbria Research Link (NRL) to enable users to access the University's research output. Copyright © and moral rights for items on NRL are retained by the individual author(s) and/or other copyright owners. Single copies of full items can be reproduced, displayed or performed, and given to third parties in any format or medium for personal research or study, educational, or not-for-profit purposes without prior permission or charge, provided the authors, title and full bibliographic details are given, as well as a hyperlink and/or URL to the original metadata page. The content must not be changed in any way. Full items must not be sold commercially in any format or medium without formal permission of the copyright holder. The full policy is available online: <http://nrl.northumbria.ac.uk/policies.html>

This document may differ from the final, published version of the research and has been made available online in accordance with publisher policies. To read and/or cite from the published version of the research, please visit the publisher's website (a subscription may be required.)

www.northumbria.ac.uk/nrl



Control strategies for brushless doubly fed reluctance machines

Authors: Milutin Jovanovic, Robert E. Betz

Abstract:

Brushless doubly-fed machines (BDFMs) have been extensively researched over the last 15 years because they allow the use of a partially rated inverter in many variable speed applications. In its cage form the machine has substantial rotor losses and compromised efficiency. However, a reluctance version of the BDFM, the brushless doubly-fed reluctance machine (BDFRM), ideally has no rotor losses and therefore offers the potential for greater efficiency and much simpler control. To date a truly comprehensive and machine independent theoretical analysis of the BDFRM's optimal control properties has not been carried out. This paper will attempt to fill this void by considering the theoretical performance limitations of various control strategies for the machine, including maximum torque per inverter ampere, maximum torque per total ampere, maximum power factor of the two windings and associated trade-offs.

Keywords: brushless, reluctance machines, optimal control