

# Northumbria Research Link

Citation: Orange, Sam, Metcalfe, James W., Liefelth, Andreas, Marshall, Phil, Madden, Leigh A., Fewster, Connor R. and Vince, Rebecca V. (2019) Validity and Reliability of a Wearable Inertial Sensor to Measure Velocity and Power in the Back Squat and Bench Press. *Journal of Strength and Conditioning Research*, 33 (9). pp. 2398-2408. ISSN 1064-8011

Published by: Lippincott Williams & Wilkins

URL: <https://doi.org/10.1519/JSC.0000000000002574>  
<<https://doi.org/10.1519/JSC.0000000000002574>>

This version was downloaded from Northumbria Research Link:  
<http://nrl.northumbria.ac.uk/id/eprint/39487/>

Northumbria University has developed Northumbria Research Link (NRL) to enable users to access the University's research output. Copyright © and moral rights for items on NRL are retained by the individual author(s) and/or other copyright owners. Single copies of full items can be reproduced, displayed or performed, and given to third parties in any format or medium for personal research or study, educational, or not-for-profit purposes without prior permission or charge, provided the authors, title and full bibliographic details are given, as well as a hyperlink and/or URL to the original metadata page. The content must not be changed in any way. Full items must not be sold commercially in any format or medium without formal permission of the copyright holder. The full policy is available online: <http://nrl.northumbria.ac.uk/policies.html>

This document may differ from the final, published version of the research and has been made available online in accordance with publisher policies. To read and/or cite from the published version of the research, please visit the publisher's website (a subscription may be required.)



1   **Validity and Reliability of a Wearable Inertial Sensor to Measure Velocity**  
2   **and Power in the Back Squat and Bench Press**

3   Samuel T. Orange<sup>1,2\*</sup>, James W. Metcalfe<sup>1,2</sup>, Andreas Liefelth<sup>2</sup>, Phil Marshall<sup>1</sup>, Leigh A.  
4   Madden<sup>3</sup>, Connor R. Fewster<sup>4</sup> and Rebecca V. Vince<sup>1</sup>.

5   <sup>1</sup>Sport, Health and Exercise Science, School of Life Sciences, University of Hull, Hull, UK.

6   <sup>2</sup>School of Sport, York St John University, York, UK.

7   <sup>3</sup>Centre of Biomedical Research, School of Life Sciences, University of Hull, Hull, UK.

8   <sup>4</sup>Carnegie School of Sport, Leeds Beckett University, Leeds, UK.

9

10   \*Corresponding author

11   Samuel T. Orange

12   <sup>1</sup>Sport, Health and Exercise Science, School of Life Sciences

13   University of Hull, Cottingham Road, Hull, UK, HU6 7RX.

14   Email: orange\_1@hotmail.co.uk

15   Telephone: +44 (0)1482 466314

16

17   *Brief running head:* Validity and reliability of an inertial sensor

18   *Disclosure statement:* This research did not receive any specific grant from funding agencies in the  
19   public, commercial, or not-for-profit sectors.

20

21 **ABSTRACT**

22 This study examined the validity and reliability of a wearable inertial sensor to measure  
23 velocity and power in the free-weight back squat and bench press. Twenty-nine youth rugby  
24 league players ( $18 \pm 1$  years) completed two test-retest sessions for the back squat followed by  
25 two test-retest sessions for the bench press. Repetitions were performed at 20%, 40%, 60%,  
26 80% and 90% of one repetition maximum (1RM) with mean velocity (MV), peak velocity (PV),  
27 mean power (MP) and peak power (PP) simultaneously measured using an inertial sensor  
28 (PUSH<sup>TM</sup>) and a linear position transducer (GymAware PowerTool). PUSH<sup>TM</sup> only  
29 demonstrated good validity (Pearson product-moment correlation coefficient [ $r$ ]) and  
30 reliability (intraclass correlation coefficient [ICC]) for measurements of MP ( $r = 0.91$ ; ICC =  
31 0.83) and PP ( $r = 0.90$ ; ICC = 0.80) at 20% of 1RM in the back squat. However, it may be more  
32 appropriate for athletes to jump off the ground with this load to optimise power output. Further  
33 research should therefore evaluate the usability of inertial sensors in the jump squat exercise.  
34 In the bench press, good validity and reliability were only evident for the measurement of MP  
35 at 40% of 1RM ( $r = 0.89$ ; ICC = 0.83). PUSH<sup>TM</sup> was unable to provide a valid and reliable  
36 estimate of any other criterion variable in either exercise. Practitioners must be cognisant of  
37 the measurement error when using inertial sensor technology to quantify velocity and power  
38 during resistance training, particularly with loads other than 20% of 1RM in the back squat and  
39 40% of 1RM in the bench press.

40 **Key words:** Linear position transducer, rugby league, sports performance, strength and  
41 conditioning.

42 **INTRODUCTION**

43 The use of velocity-based feedback has recently emerged as an effective strategy to monitor  
44 loading intensity (10, 17) and estimate the proximity of repetition failure (29) during resistance  
45 training. A progressive decline in repetition velocity is also representative of acute  
46 neuromuscular fatigue during isoinertial loading (33). Furthermore, objectively measuring  
47 mechanical power during resistance training enables the strength and conditioning (S&C)  
48 practitioner to determine the load that elicits optimal power output and quantify training-  
49 induced adaptations (40). The accurate measurement of velocity and power is contingent on  
50 the development of valid and reliable instruments that are usable in the field (2).

51 Force platforms are widely considered the gold standard for the direct acquisition of kinetic  
52 data (14). This technique may be less appropriate for measuring barbell velocity, however,  
53 because force platforms are unable to account for barbell movements that occur independent  
54 of the body (12). In addition, force platforms are generally not available for use within a  
55 practical setting (11). Linear position transducers (LPTs) are portable kinematic systems that  
56 directly measure the vertical displacement of a cable (that is attached to the barbell) and  
57 determine velocity and power through double differentiation processes (12). GymAware  
58 PowerTool (GYM) is a commercially available LPT that provides immediate kinematic  
59 feedback and automated summary reports on a cloud-based system. GYM has recently been  
60 shown to accurately assess velocity and power output in the free-weight back squat (6) and  
61 bench press (15) compared to laboratory-based criterion measures. However, the relatively  
62 high monetary cost of GYM (~£1700 per unit) limits its widespread application to all sporting  
63 organisations. The requirement of a cable attachment to the barbell also restricts the number of  
64 resistance exercises it can accurately measure. This has given rise to the increased popularity  
65 of various wearable devices to improve the accessibility of tracking kinematic and kinetic  
66 variables during resistance training.

67 A wearable inertial sensor has recently been developed (PUSH<sup>TM</sup>) to quantify movement  
68 velocity and power output in resistance training exercises. The device is relative economical  
69 (~£220 per unit) and is worn inconspicuously on the forearm. Good correlations between  
70 PUSH<sup>TM</sup> and a LPT have previously been reported for the measurement of mean and peak  
71 velocity in the Smith machine back squat (5). Sato et al. (35) also suggested that PUSH<sup>TM</sup> is  
72 highly valid at measuring movement velocity in the dumbbell biceps curl and dumbbell  
73 shoulder press. However, the Pearson correlation analyses employed in both studies (5, 35)  
74 involved combining all repetitions performed by each individual. That is, all participants  
75 provided multiple data points in each paired measure. This statistical technique, although a  
76 widespread practice, violates the assumption of independence of error between observations in  
77 the Pearson correlation analysis (4). Analysing non-independent data with techniques that  
78 assume independence often produces specious results (1, 26). Combining all repetitions for  
79 analysis also does not elucidate whether the validity of the inertial sensor is load dependent.

80 In the only other study evaluating the validity of PUSH<sup>TM</sup> to date, Banyard and colleagues (6)  
81 compared PUSH<sup>TM</sup> to a laboratory-based testing device in the free-weight back squat. Ten  
82 resistance-trained males lifted loads of 20, 40, 60, 80, 90 and 100% of one repetition maximum  
83 (1RM), with the fastest repetition from each load used for correlation analysis. Their results  
84 suggested that the validity of PUSH<sup>TM</sup> to assess velocity and power in the back squat was  
85 questionable (6). Although the data were appropriately analysed and provide useful  
86 information, the applicability of these results to athlete populations is somewhat limited  
87 because the study involved a small sample of recreationally-trained men. Athletic populations  
88 require sessional and weekly training loads to be monitored with increased precision because  
89 of a typically greater training burden and the need to prepare for competition. Within-subject  
90 variation is also likely to differ between athlete and recreational populations (21). To determine

91 the usability of PUSH™ within professional sport, it is essential to evaluate its validity in a  
92 larger sample of professional athletes.

93 Despite receiving considerable academic and practitioner interest in recent years, the test-retest  
94 reliability of the PUSH™ device is yet to be determined. Previous studies have either not  
95 employed a repeated measures design that permits a test-retest analysis (5, 35) and/or have not  
96 reported any reliability statistics (6, 35). Similarly, the smallest difference between repeated  
97 trials that is not due to measurement error or variation within individual performance, termed  
98 the smallest worthwhile change (SWC) (22), has not been established. Therefore, the purpose  
99 of this study was to evaluate the concurrent validity and test-retest reliability of a wearable  
100 inertial sensor to measure velocity and power output during the free-weight back squat and  
101 bench press in professional youth rugby league players.

102 **METHODS**

103 **Experimental Approach to the Problem**

104 Using a repeated measures design, participants visited the laboratory on five separate occasions.  
105 The first visit was a familiarisation session where 1RMs were determined for the free-weight  
106 back squat and bench press. Participants were also familiarised with executing the concentric  
107 phase of each repetition with maximal intentional velocity. Visits two and three to the  
108 laboratory involved test and retest sessions for the back squat, whereas visits four and five were  
109 test and retest sessions for the bench press. Each of these testing sessions involved the  
110 completion of repetitions at 20%, 40%, 60%, 80% and 90% of 1RM. Mean velocity (MV),  
111 peak velocity (PV), mean power (MP) and peak power (PP) of each repetition were  
112 simultaneously recorded using a commercially available LPT (GymAware PowerTool [GYM],  
113 Kinetic Performance Technologies, Canberra, Australia) and a wearable inertial sensor

114 (PUSH<sup>TM</sup>, PUSH Inc., Toronto, Canada). Before each visit to the laboratory, participants were  
115 instructed to refrain from caffeine for  $\geq 12$  hours and strenuous physical activity for  $\geq 24$  hours.

116 **Subjects**

117 Twenty-nine professional male youth rugby league players (age:  $18 \pm 1$  years [range: 16 to 19  
118 years]; height:  $1.73 \pm 0.83$  m; body mass:  $87.3 \pm 20.8$  kg) from an English Super League club's  
119 academy volunteered to participate in this study. Players reported engaging in structured  
120 resistance training  $4.3 \pm 0.5$  times per week for  $3.1 \pm 1.3$  years before the commencement of  
121 the study. Player strength characteristics are presented in Table 1. All participants were  
122 informed of the experimental procedures to be undertaken prior to signing an institutionally  
123 approved informed consent document to participate in the study. Parental or guardian signed  
124 consent was also obtained for participants aged  $< 18$  years. Ethical approval for the study was  
125 granted by the Sports, Health and Exercise Science Ethics Committee at the University of Hull.

126 **[INSERT TABLE 1 ABOUT HERE]**

127 **Procedures**

128 **1RM testing**

129 1RM testing was consistent with recognised guidelines established by the National Strength  
130 and Conditioning Association (18). A UKSCA accredited S&C coach and a Certified Strength  
131 and Conditioning Specialist (CSCS) were present at all testing sessions to ensure correct  
132 technique and adherence to the 1RM protocol. For the back squat, an Olympic barbell was  
133 placed on the trapezius in a high-bar position. With their feet externally rotated  $5\text{--}10^\circ$  and  
134 placed shoulder-width apart, participants started in an upright bipedal position and descended  
135 downwards until the top of the thigh was at least parallel to the floor before returning to the  
136 starting position. Participants were required to maintain constant downward pressure on the  
137 barbell (13) and keep their feet in contact with the floor during all repetitions. Bench press

138 1RM testing was performed on a solid flat bench secured in position inside an adjustable power  
139 rack (Perform Better Ltd, Southam, UK). The position of the bench was individually adjusted  
140 so that the vertical trajectory of the barbell was in line with participants' intermammary line.  
141 Participants unracked the barbell using a self-selected grip width and lay supine on the bench  
142 with their arms fully extended. Upon verbal command, participants lowered the barbell until  
143 the chest was briefly touched, approximately 3 cm superior to the xiphoid process, before  
144 executing full elbow extension. The attempt was considered successful if the participant's head,  
145 upper back, and buttocks remained firmly placed on the bench and both feet stayed flat on the  
146 floor. The barbell was not permitted to bounce off the chest. Participants performed the  
147 eccentric phase of both exercises in a controlled manner at a self-selected velocity and  
148 completed the concentric phase as fast as possible.

149 **Test-retest sessions**

150 All test and retest sessions were conducted at the same time of day (7 a.m.) and were separated  
151 by seven days. Following a standardised warm-up protocol, participants completed three  
152 consecutive repetitions at loads of 20%, 40%, 60% and 80% of 1RM, and two repetitions at  
153 90% of 1RM. These loads were chosen to represent the full loading spectrum and to aid  
154 comparisons with previous studies (5, 6). Three minutes of passive rest were provided between  
155 different loading conditions and participants were verbally encouraged to execute each  
156 repetition with maximal concentric velocity. Additional repetitions were performed if technical  
157 lifting requirements were not met or submaximal effort was used, as determined by a consensus  
158 from the UKSCA accredited S&C coach and CSCS. GYM was considered the criterion in this  
159 study because the device has previously been shown to accurately assess velocity and power  
160 in the back squat (6) and bench press (15).

161 **Data analysis**

162 GYM is a commercially available LPT consisting of a floor unit, made up of a steel cable that  
163 is wound on a cylindrical spool coupled to the shaft of an optical encoder (15). The floor unit  
164 was placed on the floor perpendicular to the right collar of the barbell. In line with  
165 manufacturer's instructions, the other end of the cable was vertically attached to the barbell  
166 (immediately proximal to the right collar) using a Velcro strap. GYM measures the vertical  
167 displacement of its cable in response to changes in barbell position. The displacement data  
168 were time-stamped at 20 millisecond time points and down-sampled to 50 Hz for analysis. The  
169 sampled data were not filtered. Instantaneous velocity was determined as the change in barbell  
170 position with respect to time. Acceleration data were calculated as the change in barbell  
171 velocity over the change in time for each consecutive data point. Instantaneous force was  
172 determined by multiplying the system mass with acceleration, where system mass was the  
173 barbell load plus the relative body mass of the participant (6). Power was then calculated as the  
174 product of force and velocity. Data obtained from GYM were transmitted via Bluetooth to a  
175 tablet (iPad, Apple Inc., California, USA) using the GymAware v2.1.1 app.

176 PUSH<sup>TM</sup> is a wearable inertial sensor consisting of a 3-axis accelerometer and a gyroscope that  
177 provides six degrees in its coordinate system. The device was worn on the participant's right  
178 forearm, 1-2 cm distal to the elbow crease, with the main button located proximally as per  
179 manufacturer's instruction. The acceleration data were smoothed using a Butterworth filter,  
180 and vertical velocity was calculated by the integration of acceleration with respect to time.  
181 Similarly to GYM, instantaneous force was calculated as the product of acceleration and the  
182 system mass, and power was determined by multiplying force with velocity. Data obtained  
183 from PUSH<sup>TM</sup> were recorded at a sampling rate of 200 Hz and transmitted to the PUSH<sup>TM</sup>  
184 v3.1.2 app via a Bluetooth connection with a tablet. PUSH<sup>TM</sup> and GYM do not require  
185 calibration processes.

186 The participant's body mass and the barbell load used were entered into both apps prior to each  
187 repetition. Values of MV and MP obtained by the PUSH<sup>TM</sup> and GYM were determined as the  
188 average of all the instantaneous data collected during the concentric phase of each repetition.  
189 PV and PP were calculated as the maximum value registered during the same concentric period.  
190 The maximum value of each set of repetitions performed at each load (fastest mean concentric  
191 velocity as determined by GYM) was used for analysis.

192 **Statistical analysis**

193 All data were analysed using custom-designed Microsoft Excel spreadsheets (Microsoft  
194 Corporation, Redmond, Washington, USA) (24). The concurrent validity and test-retest  
195 reliability of PUSH<sup>TM</sup> were determined by examining each relative load separately (i.e. 20%,  
196 40%, 60%, 80%, and 90% of 1RM). Validity of PUSH<sup>TM</sup> was assessed using the Pearson  
197 product-moment correlation coefficient (Pearson's *r*) and mean bias with 95% limits of  
198 agreement (95% LOA). The standardised mean bias was rated as: trivial (<0.2), small, (0.2 to  
199 0.59), moderate (0.6 to 1.19), large (1.2 to 1.99), very large (2.0 to 3.99) and extremely large  
200 ( $\geq 4.0$ ) (24). Relative reliability was determined using the intraclass correlation coefficient  
201 (ICC). Absolute reliability was examined using the standard error of measurement (SEM) and  
202 the smallest worthwhile change (SWC). SEM was calculated using the formula  $SD_{diff}/\sqrt{2}$  (22)  
203 and was also expressed as a percentage of the mean (SEM%). The SWC was calculated as the  
204 between-subject SD multiplied by 0.2 (22). The following criteria were used to interpret the  
205 strength of the Pearson's *r* used to assess validity and the ICC estimates used to assess  
206 reliability: poor (<0.5), moderate (0.50 to 0.74), good (0.75 to 0.89) and excellent ( $\geq 0.9$ ) (27).  
207 The level for all confidence intervals (CI) was set at 95%.

208 **RESULTS**

209 Figure 1 presents velocity and power data across each relative intensity. The reliability (ICC,  
210 SEM%) of MV measurements obtained by GYM ranged from 0.72 to 0.87 and 3.9 to 9.9%,  
211 respectively.

212 [INSERT FIGURE 1 ABOUT HERE]

213 [INSERT TABLE 2 ABOUT HERE]

214 **Back squat**

215 The standardised mean bias showed small differences between PUSH<sup>TM</sup> and GYM devices for  
216 the measurement of PV and MP at 20% of 1RM. There were moderate to very large  
217 underestimations of all other criterion variables (see Table, Supplemental Digital Content 1),  
218 which were also evidenced by the 95% LOA (Figures 2 to 5). Despite the evidence of  
219 systematic bias, good to excellent correlations ( $r \geq 0.75$ ) were found between PUSH<sup>TM</sup> and  
220 GYM methods for MP and PP measurements at loads of 20% to 80% of 1RM. Good  
221 correlations were also found for MV at 20%, 60%, and 80% of 1RM, and PV at 20% and 80%  
222 of 1RM.

223 PUSH<sup>TM</sup> only demonstrated good reliability for the measurement of MP (ICC = 0.83, 95% CI:  
224 0.66 to 0.91) and PP (ICC = 0.80, 95% CI: 0.62 to 0.90) at 20% of 1RM. The SEM% and ICC  
225 estimates tended to worsen as the relative intensity increased (Figures 2 to 5). Absolute SEM  
226 and SWC data for all measurements obtained by PUSH<sup>TM</sup> are presented in Table 2.

227 **Bench press**

228 The standardised mean bias showed that there were no obvious under- or over-estimations of  
229 PV at 60% to 90% of 1RM and MP at 60% of 1RM. Small systematic biases were evident for  
230 the measurements of MV at 60% of 1RM, PV and MP at 20% and 40% of 1RM, and PP at 90%  
231 of 1RM. There were moderate differences between PUSH<sup>TM</sup> and GYM for all other criterion

232 variables (see Table, Supplemental Digital Content 1). Good correlations between PUSH<sup>TM</sup>  
233 and GYM were found for the measurement of MV at 40% of 1RM ( $r = 0.84$ , 95% CI: 0.68 to  
234 0.92), and for MP at 40% ( $r = 0.89$ , 95% CI: 0.77 to 0.95) and 80% ( $r = 0.76$ , 95% CI: 0.53 to  
235 0.88) of 1RM.

236 PUSH<sup>TM</sup> only showed good reliability for the measurement of MP (ICC = 0.83, 95% CI: 0.67  
237 to 0.92) and PP (ICC = 0.88, 95% CI: 0.76 to 0.94) at 40% of 1RM.

238 [INSERT FIGURE 2 ABOUT HERE]

239 [INSERT FIGURE 3 ABOUT HERE]

240 [INSERT FIGURE 4 ABOUT HERE]

241 [INSERT FIGURE 5 ABOUT HERE]

242

## 243 DISCUSSION

244 This study examined the validity and reliability of a wearable inertial sensor (PUSH<sup>TM</sup>) to  
245 measure velocity and power in the back squat and bench press. Our data are the first to  
246 demonstrate that the reliability and validity of PUSH<sup>TM</sup> are contingent on the exercise and the  
247 external load lifted. The device was reliable and valid for the measurements of MP at 20% of  
248 1RM in the back squat. In the bench press, PUSH<sup>TM</sup> provided a reliable and valid measurement  
249 of MP at 40% of 1RM.

250 This study is the first to determine the test-retest reliability of PUSH<sup>TM</sup>. In the free-weight back  
251 squat, there was evidence of good reliability for the measurement of MP (ICC = 0.83, 95% CI:  
252 0.66 to 0.91) and PP (ICC = 0.80, 95% CI: 0.62 to 0.90) at 20% of 1RM. The 95% CIs of these  
253 ICC estimates suggest that the true reliability for this population likely ranges from moderate  
254 to excellent. Interestingly though, our data demonstrated that the reliability of the device tended

255 to decrease as the external load increased, as evidenced by both the SEM% and ICC data  
256 (Figures 2 to 5). This finding aligns well with a recent study (8) reporting a trend of greater  
257 between-subject variation in MV and MP with increasing relative intensities in the back squat.  
258 This inverse relationship between reliability and intensity may be attributed to alterations in  
259 lower body kinematics with increasing loads. Kellis and colleagues (25) reported a 16° increase  
260 in forward trunk inclination between 40-70% of 1RM in the free-weight back squat. Hay and  
261 colleagues (20) also found that the absolute angle of the hip increased significantly by 22° when  
262 the external load was increased from 40% to 80% of 4RM, possibly due to greater involvement  
263 of the hip musculature and a concomitant reduction in knee extensor torque (20). Although  
264 technique and squat depth were vigilantly monitored throughout testing, this intrinsic change  
265 in lower body kinematics would conceivably alter the pathway and orientation of the inertial  
266 sensor during the squat movement. Similarly, in the bench press, horizontal displacement of  
267 the barbell has been shown to significantly increase from  $86 \pm 36$  mm at 70% of 1RM to  $123 \pm 38$  mm at 100% of 1RM (28). Greater horizontal displacement of the barbell at heavier loads  
268 may result from an increased effort to reduce the moment arm about the shoulder axis (16, 28),  
269 which would alter the position of the forearm relative to the barbell during the concentric phase.  
270 Caution should therefore be taken when measuring velocity and power at heavier loads in free-  
271 weight resistance exercises.

273 We have provided absolute measures of reliability to enable practitioners to interpret whether  
274 training-induced changes in velocity and/or power are practically significant. The SEM  
275 represents the typical variation in performance from repeated trials and displays measurement  
276 error in the same units as the original measurement (22). It is important for coaches to minimise  
277 the SEM in order to detect subtle yet meaningful changes in performance. Sánchez-Medina et  
278 al. (34) have eloquently shown that differences in MV between each 5% increment in relative  
279 load vary between  $0.05$  and  $0.10 \text{ m} \cdot \text{s}^{-1}$  in the back squat. Their data also show that for each 10%

280 increase in load, the concomitant change in MV varies between 0.11 and 0.18 m·s<sup>-1</sup> (34). Based  
281 on the SEM values for MV reported in this study (Table 2), the inertial sensor appears reliable  
282 enough to detect 10%, but not 5%, changes in relative load. S&C practitioners must judge  
283 whether the magnitude of measurement error is acceptable based on the specific needs of their  
284 athletes. Clearly, an appropriate balance must be struck between usability, cost, practicality,  
285 and reliability of the testing method.

286 Two previous studies have supported the use of PUSH<sup>TM</sup> to accurately measure movement  
287 velocity during resistance training. Sato and colleagues (35) reported good correlations  
288 between PUSH<sup>TM</sup> and a 3D motion analysis capture system for the measurement of MV and  
289 PV in the dumbbell biceps curl (MV:  $r = 0.86$ ; PV:  $r = 0.80$ ) and shoulder press (MV:  $r = 0.88$ ;  
290 PV:  $r = 0.92$ ). Using a LPT as the criterion measure, Balsalobre-Fernández and colleagues (5)  
291 also suggested that PUSH<sup>TM</sup> was highly valid at measuring MV ( $r = 0.85$ ) and PV ( $r = 0.91$ ) in  
292 the Smith machine back squat. Unlike the free-weight back squat though, the Smith machine  
293 restricts barbell displacement to a fixed linear path, which eliminates measurement error  
294 resulting from extraneous horizontal motion (12). Furthermore, the Pearson correlation  
295 analyses employed in both studies (5, 35) involved combining all repetitions performed by each  
296 individual. For example, participants in the Balsalobre-Fernández et al. (5) study performed  
297 three repetitions at loads of 20, 40, 50, 60 and 70kg, with each repetition used in the validity  
298 analyses. Therefore, all participants provided 15 data points in each paired sample. This  
299 technique violates the assumption of independence in the Pearson correlation analysis and is  
300 likely to produce erroneous results (4).

301 To satisfy the assumption of independence, we analysed each relative load separately using the  
302 fastest repetition at each load. Our data demonstrated good to excellent correlations between  
303 PUSH<sup>TM</sup> and GYM for MP and PP measurements at loads of 20% to 80% of 1RM. We also  
304 found good correlations for measurements of MV at 20%, 60% and 80% of 1RM and for PV

305 at 20% and 80% of 1RM. Similarly, Banyard and colleagues (6) recently reported that PUSH<sup>TM</sup>  
306 was highly valid for the measurement of MV at light to moderate loads (i.e. <60% of 1RM)  
307 and for measuring PV at light loads (i.e. 20% of 1RM). However, they considered all MP and  
308 PP data obtained by PUSH<sup>TM</sup> to be invalid. Differences between these results and our data are  
309 readily explained by the different validity criteria used. We employed Pearson's *r* to determine  
310 thresholds of acceptable validity, whereas Banyard and colleague's (6) included Pearson's *r*,  
311 coefficient of variation (CV) and the effect size in their validity criteria. Interestingly, if the  
312 CV was not used in their (6) analyses, the validity of PUSH<sup>TM</sup> to measure MP and PP would  
313 have been considered high for all loads except for 90% and 100% of 1RM (i.e. the same results  
314 as the present study). Although the CV is commonly used to assess the validity of variables  
315 pertinent to sports medicine (3), it has been suggested that this statistic may be more  
316 representative of variability within an individual, rather than within a sample of individuals  
317 (30). This appears logical given the CV can only be directly calculated from repeated  
318 measurements on a single case (32). Additional differences between studies include the  
319 criterion measure used, the number of repetitions performed per load, and the sample  
320 population (and therefore the sample heterogeneity).

321 Though the inertial sensor was valid and reliable for measuring MP at 20% of 1RM in the back  
322 squat, the practical applications of prescribing this load are questionable. We instructed  
323 participants to keep their feet in contact with the floor during all repetitions in order to  
324 standardise technique between each load. Due to the inherent limitation of applying maximal  
325 force to the ground when using light loads in the back squat (34), it may be more appropriate  
326 for athletes to jump off the ground with 20% of 1RM. Indeed, peak power output in the jump  
327 squat has been shown to be approximately twofold greater compared with the back squat (13).  
328 Lighter loads ( $\leq 30\%$  of 1RM) also elicit the highest PP output in the jump squat exercise (36).

329 Therefore, further research should evaluate the validity and reliability of inertial sensors to  
330 measure power in the jump squat.

331 In agreement with previous reports (5), we found evidence of systematic bias between the  
332 inertial sensor and LPT in the back squat. Specifically, the standardised mean bias showed  
333 moderate to very large underestimations of most criterion variables, which were also evidenced  
334 by the 95% LOA. This bias is likely underpinned by differences in calculation techniques.  
335 GYM is a portable LPT that directly measures the vertical displacement of its cable. Movement  
336 velocity and power output are calculated as derivatives of the displacement data through double  
337 differentiation processes. Conversely, the inertial sensor is worn on the forearm and  
338 encompasses a 3-axis accelerometer with a gyroscope. Differentiation of the acceleration data  
339 then permits the calculation of velocity and power. The differentiation procedures used by both  
340 systems, although based on well-established mathematical principles, require extensive data  
341 manipulation and therefore result in the amplification of noise and the consequential risk of  
342 erroneous data (12). Inertial sensors and LPTs also use different sampling frequencies and  
343 methods to correct for motion in the horizontal plane, which may further contribute to the  
344 systematic bias. The lack of agreement between PUSH<sup>TM</sup> and GYM suggests that S&C  
345 practitioners should not use these two devices interchangeably and should take caution when  
346 comparing data obtained by inertial sensors to normative data obtained by LPTs in the literature.

347 The inertial sensor showed good reliability for the measurement of MP (ICC = 0.83, 95% CI:  
348 0.67 to 0.92) and PP (ICC = 0.88, 95% CI: 0.76 to 0.94) at 40% of 1RM in the bench press. In  
349 addition, a good correlation between PUSH<sup>TM</sup> and GYM was found at 40% of 1RM for the  
350 measurement of MP ( $r = 0.89$ , 95% CI 0.77 to 0.95), with the lower 95% CI of the Pearson  
351 correlation also exceeding the threshold for good validity. Furthermore, the mean bias with 95%  
352 LOA for this measurement were relatively narrow ( $32.3 \pm 95.3$  W), with the standardised mean  
353 bias demonstrating only a small underestimation (0.31) compared to GYM. Therefore, these

354 data suggest that PUSH<sup>TM</sup> provides a reliable and valid measurement of MP at 40% of 1RM. It  
355 is important to note that maximal MP and PP output were also achieved at 40% of 1RM (Figure  
356 1), which is in agreement with previous research demonstrating that power production in the  
357 bench press is optimised at moderate loads (37). This finding indicates that S&C coaches are  
358 able to prescribe 40% of 1RM in the bench press to accurately quantify and develop the power-  
359 generating capabilities of their athletes.

360 The criteria for ICC estimates of reliability used in this study were based on recent guidelines  
361 for selecting and reporting ICCs (27). For example, an ICC estimate of 0.75 or above was  
362 considered a good level of reliability. We also used the same thresholds for Pearson correlations  
363 to improve clarity in the interpretation of our data. Many studies (19, 31, 38, 39) have used a  
364 correlation threshold of  $\geq 0.50$  to denote a strong level of validity and/or reliability based on  
365 criteria put forward by Cohen (9) and Hopkins (23). On the other hand, some authors have  
366 chosen an analytic goal of  $r$  being above 0.70 (6, 7). We have provided mean estimates with  
367 95% CIs for all correlation coefficients to enable the reader to make their own interpretation of  
368 the data.

369 In conclusion, these data show that the reliability and validity of the inertial sensor are  
370 contingent on the exercise and the external load lifted. The PUSH<sup>TM</sup> device was reliable and  
371 valid for the measurement of MP at light relative loads (e.g. 20% of 1RM) in the back squat.  
372 However, the practical applications of using this load are questionable because of the intrinsic  
373 limitation of applying maximal force to the ground when lifting light loads in the back squat.  
374 In the bench press, PUSH<sup>TM</sup> obtained a valid and reliable measurement of MP at 40% of 1RM,  
375 although a small systematic bias between PUSH<sup>TM</sup> and GYM devices was present. Practitioners  
376 must be cognisant of the measurement error when evaluating changes in performance between  
377 repeated trials.

378 **PRACTICAL APPLICATIONS**

379 Though the inertial sensor was considered valid and reliable for measuring MP at 20% of 1RM  
380 in the back squat, it may be more appropriate for athletes to jump off the ground with this load  
381 in order to optimise power output. Further research should therefore evaluate the validity and  
382 reliability of inertial sensors to measure power in the jump squat exercise. Measuring MP at  
383 40% of 1RM provides S&C coaches with a reliable and valid measurement of power output in  
384 the bench press. However, inertial sensors and LPTs should not be used interchangeably  
385 because of the systematic bias between the two systems. Practitioners should acknowledge the  
386 magnitude of measurement error between repeated trials when using inertial sensor technology  
387 to quantify velocity and power in resistance training exercises.

388 **References**

- 389  
390 1. Aarts E, Verhage M, Veenvliet JV, Dolan CV, van der Sluis S. A solution to dependency: using multilevel analysis to accommodate nested data. *Nat Neurosci.* 2014;17(4):491-6.  
391  
392  
393 2. Abernethy P, Wilson G, Logan P. Strength and power assessment. Issues, controversies and challenges. *Sports Med.* 1995;19(6):401-17.  
394  
395 3. Atkinson G, Nevill AM. Statistical methods for assessing measurement error (reliability) in variables relevant to sports medicine. *Sports Med.* 1998;26(4):217-38.  
396  
397 4. Bakdash JZ, Marusich LR. Repeated Measures Correlation. *Front Psychol.* 2017;8:456.  
398  
399 5. Balsalobre-Fernandez C, Kuzdub M, Poveda-Ortiz P, Campo-Vecino JD. Validity and Reliability of the PUSH Wearable Device to Measure Movement Velocity During the Back Squat Exercise. *J Strength Cond Res.* 2016;30(7):1968-74.  
400  
401 6. Banyard HG, Nosaka K, Sato K, Haff GG. Validity of Various Methods for Determining Velocity, Force and Power in the Back Squat. *Int J Sports Physiol Perform.* 2017;1:25.  
402  
403 7. Bishop D, Spencer M, Duffield R, Lawrence S. The validity of a repeated sprint ability test. *J Sci Med Sport.* 2001;4(1):19-29.  
404  
405 8. Carroll KM, Sato K, Bazyler CD, Triplett NT, Stone MH. Increases in Variation of Barbell Kinematics Are Observed with Increasing Intensity in a Graded Back Squat Test. *Sports.* 2017;5(3):51.  
406  
407 9. Cohen J. *Statistical Power Analysis for the Behavioral Sciences*. New York, NY: Routledge Academic; 1988.  
408  
409 10. Conceicao F, Fernandes J, Lewis M, Gonzalez-Badillo JJ, Jimenez-Reyes P. Movement velocity as a measure of exercise intensity in three lower limb exercises. *J Sports Sci.* 2016;34(12):1099-106.  
410  
411 11. Cormie P, Deane R, McBride JM. Methodological concerns for determining power output in the jump squat. *J Strength Cond Res.* 2007;21(2):424-30.  
412  
413 12. Cormie P, McBride JM, McCaulley GO. Validation of power measurement techniques in dynamic lower body resistance exercises. *J Appl Biomech.* 2007;23(2):103-18.  
414  
415 13. Cormie P, McCaulley GO, Triplett NT, McBride JM. Optimal loading for maximal power output during lower-body resistance exercises. *Med Sci Sports Exerc.* 2007;39(2):340-9.  
416  
417 14. Crewther BT, Kilduff LP, Cunningham DJ, Cook C, Owen N, Yang GZ. Validating two systems for estimating force and power. *Int J Sports Med.* 2011;32(4):254-8.  
418  
419 15. Drinkwater EJ, Galna B, McKenna MJ, Hunt PH, Pyne DB. Validation of an optical encoder during free weight resistance movements and analysis of bench press sticking point power during fatigue. *J Strength Cond Res.* 2007;21(2):510-7.  
420  
421 16. Elliott BC, Wilson GJ, Kerr GK. A biomechanical analysis of the sticking region in the bench press. *Med Sci Sports Exerc.* 1989;21(4):450-62.  
422  
423 17. Gonzalez-Badillo JJ, Sanchez-Medina L. Movement velocity as a measure of loading intensity in resistance training. *Int J Sports Med.* 2010;31(5):347-52.  
424  
425 18. Haff G, G., Triplett TN. *Essentials of Strength Training and Conditioning*. Champaign, IL: Human Kinetics; 2015.  
426  
427 19. Harper LD, Hunter R, Parker P, Goodall S, Thomas K, Howatson G, et al. Test-Retest Reliability of Physiological and Performance Responses to 120 Minutes of Simulated Soccer Match Play. *J Strength Cond Res.* 2016;30(11):3178-86.  
428  
429 20. Hay JG, Andrews JG, Vaughan CL, Ueya K. Load, speed and equipment effects in strength-training exercises. In: Matsui H, Kobayashi K, editors. *Biomechanics VIII-B*. Champaign, IL: Human Kinetics; 1983. p. 939–50.  
430  
431  
432  
433  
434  
435  
436  
437

- 438 21. Hopkins WG, Hawley JA, Burke LM. Design and analysis of research on sport  
439 performance enhancement. *Med Sci Sports Exerc.* 1999;31(3):472-85.
- 440 22. Hopkins WG. Measures of reliability in sports medicine and science. *Sports Med.*  
441 2000;30(1):1-15.
- 442 23. Hopkins WG. A new view of statistics. Internet Society for Sport Science:  
443 <http://www.sportsci.org/resource/stats/>. 2000.
- 444 24. Hopkins WG. Spreadsheets for analysis of validity and reliability. *Sportscience.*  
445 2015;19:36-42.
- 446 25. Kellis E, Arambatzi F, Papadopoulos C. Effects of load on ground reaction force and  
447 lower limb kinematics during concentric squats. *J Sports Sci.* 2005;23(10):1045-55.
- 448 26. Kenny DA, Judd CM. Consequences of violating the independence assumption in  
449 analysis of variance. *Psychol Bull.* 1986;99(3):422-31.
- 450 27. Koo TK, Li MY. A Guideline of Selecting and Reporting Intraclass Correlation  
451 Coefficients for Reliability Research. *Journal of Chiropractic Medicine.* 2016;15(2):155-63.
- 452 28. Krol H, Golas A. Effect of Barbell Weight on the Structure of the Flat Bench Press. *J*  
453 *Strength Cond Res.* 2017;31(5):1321-37.
- 454 29. Morán-Navarro R, Martínez-Cava A, Sánchez-Medina L, Mora-Rodríguez R,  
455 González-Badillo JJ, Pallarés JG. Movement velocity as a measure of level of effort during  
456 resistance exercise. *J Strength Cond Res.* 2017.
- 457 30. Quan H, Shih WJ. Assessing reproducibility by the within-subject coefficient of  
458 variation with random effects models. *Biometrics.* 1996;52(4):1195-203.
- 459 31. Roe G, Darrall-Jones J, Black C, Shaw W, Till K, Jones B. Validity of 10-HZ GPS and  
460 Timing Gates for Assessing Maximum Velocity in Professional Rugby Union Players. *Int J*  
461 *Sports Physiol Perform.* 2017;12(6):836-9.
- 462 32. Sale DG. Testing strength and power. In: MacDougall JD, Wenger HA, Green HJ,  
463 editors. *Physiological testing of the high performance athlete.* Champaign, IL: Human Kinetics;  
464 1991. p. 21-106.
- 465 33. Sanchez-Medina L, Gonzalez-Badillo JJ. Velocity loss as an indicator of  
466 neuromuscular fatigue during resistance training. *Med Sci Sports Exerc.* 2011;43(9):1725-34.
- 467 34. Sánchez-Medina L, Pallarés JG, Pérez CE, Morán-Navarro R, González-Badillo JJ.  
468 Estimation of relative load from bar velocity in the full back squat exercise. *Sports Medicine*  
469 *International Open.* 2017;1(02):E80-E8.
- 470 35. Sato KK, Beckham G, Carroll K, Bazyler C, Sha Z, Haff GG. Validity of wireless  
471 device measuring velocity of resistance exercises. *Journal of Trainology.* 2015;4(1):15-8.
- 472 36. Soriano MA, Jimenez-Reyes P, Rhea MR, Marin PJ. The Optimal Load for Maximal  
473 Power Production During Lower-Body Resistance Exercises: A Meta-Analysis. *Sports Med.*  
474 2015;45(8):1191-205.
- 475 37. Soriano MA, Suchomel TJ, Marin PJ. The Optimal Load for Maximal Power  
476 Production During Upper-Body Resistance Exercises: A Meta-Analysis. *Sports Med.*  
477 2017;47(4):757-68.
- 478 38. Veugelers KR, Naughton GA, Duncan CS, Burgess DJ, Graham SR. Validity and  
479 Reliability of a Submaximal Intermittent Running Test in Elite Australian Football Players. *J*  
480 *Strength Cond Res.* 2016;30(12):3347-53.
- 481 39. Weaving D, Whitehead S, Till K, Jones B. Validity of Real-Time Data Generated by a  
482 Wearable Microtechnology Device. *J Strength Cond Res.* 2017;31(10):2876-9.
- 483 40. Wilson GJ, Newton RU, Murphy AJ, Humphries BJ. The optimal training load for the  
484 development of dynamic athletic performance. *Med Sci Sports Exerc.* 1993;25(11):1279-86.

485

486 **Figure and Table Captions**

487 **Table 1.** Baseline strength characteristics of study participants.

488 **Table 2.** Absolute reliability of the wearable inertial sensor in the back squat and bench press

489 **Figure 1.** Values for mean velocity (A and B), peak velocity (C and D), mean power (E and F)  
490 and peak power (G and H) in the back squat and bench press. Data are presented as means  $\pm$   
491 SD.

492 **Figure 2.** Validity and reliability of the wearable inertial sensor to measure mean velocity in  
493 the back squat and bench press. Validity was assessed using Pearson product-moment  
494 correlation coefficient (A) and the mean bias with 95% limits of agreement (B). Reliability was  
495 determined using the intraclass correlation coefficient (C) and standard error of measurement  
496 as a percentage of the mean (D). Area shaded in grey represents a good level of  
497 validity/reliability. 1RM = one repetition maximum. Data are presented as means  $\pm$  95%  
498 confidence intervals.

499 **Figure 3.** Validity and reliability of the wearable inertial sensor to measure peak velocity in  
500 the back squat and bench press. Validity was assessed using Pearson product-moment  
501 correlation coefficient (A) and the mean bias with 95% limits of agreement (B). Reliability was  
502 determined using the intraclass correlation coefficient (C) and standard error of measurement  
503 as a percentage of the mean (D). Area shaded in grey represents a good level of  
504 validity/reliability. 1RM = one repetition maximum. Data are presented as means  $\pm$  95%  
505 confidence intervals.

506 **Figure 4.** Validity and reliability of the wearable inertial sensor to measure mean power in the  
507 back squat and bench press. Validity was assessed using Pearson product-moment correlation  
508 coefficient (A) and the mean bias with 95% limits of agreement (B). Reliability was determined  
509 using the intraclass correlation coefficient (C) and standard error of measurement as a

510 percentage of the mean (D). Area shaded in grey represents a good level of validity/reliability.

511 1RM = one repetition maximum. Data are presented as means  $\pm$  95% confidence intervals.

512 **Figure 5.** Validity and reliability of the wearable inertial sensor to measure peak power in the  
513 back squat and bench press. Validity was assessed using Pearson product-moment correlation  
514 coefficient (A) and the mean bias with 95% limits of agreement (B). Reliability was determined  
515 using the intraclass correlation coefficient (C) and standard error of measurement as a  
516 percentage of the mean (D). Area shaded in grey represents a good level of validity/reliability.

517 1RM = one repetition maximum. Data are presented as means  $\pm$  95% confidence intervals.

518

519    **Supplemental Digital Content 1.** Standardised mean bias between PUSH<sup>TM</sup> and GYM

520    methods

**Table 1.** Baseline strength characteristics of study participants

Back Squat (kg)		Bench Press (kg)	
1RM	Relative 1RM	1RM	Relative 1RM
145.5 ± 24.4	1.71 ± 0.35	100.8 ± 16.4	1.18 ± 0.26

1RM = one repetition maximum; relative 1RM = one repetition


maximum normalised to body mass. Data are presented as means ±


SD.

**Table 2.** Absolute reliability of the wearable inertial sensor in the back squat and bench press

		Back Squat					Bench Press				
		20%	40%	60%	80%	90%	20%	40%	60%	80%	90%
<b>MV</b> <b>(m·s<sup>-1</sup>)</b>	SEM	0.08	0.07	0.06	0.06	0.06	0.11	0.08	0.08	0.06	0.05
	SWC	0.03	0.02	0.02	0.02	0.01	0.03	0.02	0.02	0.02	0.01
<b>PV</b> <b>(m·s<sup>-1</sup>)</b>	SEM	0.12	0.18	0.11	0.11	0.12	0.21	0.11	0.12	0.08	0.10
	SWC	0.04	0.04	0.03	0.03	0.02	0.05	0.04	0.04	0.02	0.02
<b>MP</b> <b>(W)</b>	SEM	128.3	121.5	105.9	129.5	117.0	70.6	33.8	51.6	51.3	45.7
	SWC	59.1	41.6	32.4	32.9	30.0	19.0	20.3	18.2	15.6	15.5
<b>PP</b> <b>(W)</b>	SEM	261.2	345.8	279.4	345.4	359.5	221.9	151.0	273.0	137.5	131.9
	SWC	112.3	115.6	95.9	80.7	87.5	71.1	84.2	69.2	40.0	40.8


MV = mean velocity; PV = peak velocity; MP = mean power; PP = peak power; SEM = standard error of measurement; SWC = smallest worthwhile change.







### Peak velocity

● Back Squat      □ Bench Press







**Supplemental Digital Content 1.** Standardised mean bias between PUSH<sup>TM</sup> and GYM methods

	Back Squat					Bench Press				
	20%	40%	60%	80%	90%	20%	40%	60%	80%	90%
<b>MV (m·s<sup>-1</sup>)</b>	0.61	1.17	1.41	2.23	2.61	1.06	0.68	0.55	1.03	1.12
<b>PV (m·s<sup>-1</sup>)</b>	0.53	1.20	1.58	2.23	2.74	0.55	0.37	0.18	0.00	0.10
<b>MP (W)</b>	0.51	1.10	1.73	2.24	2.08	0.35	0.31	0.00	0.64	0.60
<b>PP (W)</b>	1.20	1.01	1.39	1.43	1.59	0.74	0.73	0.70	0.88	0.48

MV = mean velocity; PV = peak velocity; MP = mean power; PP = peak power. Standardised mean bias of <0.2, 0.2 to 0.59, 0.6 to 1.19, 1.2 to 1.99, 2.0 to 3.99 and  $\geq 4.0$  were considered trivial, small, moderate, large, very large and extremely large, respectively.